





Features	SL3L
Automation type	LIGHT
Max product dimensions: Height x Depth x Maximum length	100 x 148 x 6600 mm
Maximum weight of door 1 leaf: Maximum weight of door 2 leaves:	70 kg (S3 = 100%) 2 x 50 kg (S3 = 100%) / 2 x 60 kg (S3 = 80%)
Maximum opening and closing speed: Sliding door 1 door Sliding door 2 doors	0,8 m/s 1,6 m/s
Duty class Intermittent operation	Continuous operation S3 = 100% (2 x 50 kg) / S3 = 80% (2 x 60 kg)
Internal durability test Direct-drive brushless motor with no reduction gear unit	 
Power supply Rated power Stand-by	100–240 Vac 50/60 Hz 60 W 8 W
Rated load	80 N
Protection Rating	IP 20
Operating temperature	 -15 °C  +50 °C
Parameter adjustment	Buttons and Display
Connections to control and safety devices	Dedicated connecting terminals
Number of programmable terminals	2 (G1, G2)
Power output for accessories	12 Vdc (1 A max)
Memory for settings and data saving	USB standard
Electronic function selector	FSD5, FSD6
Locking device	SL3LD, SL3SB1
Battery power device for emergency opening	SL3BD1
Fixing device for opening and safety sensor	SL3FS