

Features	SL4A	SL4E
Automation type	ADVANCED	EMERGENCY
TÜV Thüringen certification		
Product dimensions: Height x Depth x Max length	125 x 156 x 6600 mm	125 x 156 x 6600 mm
Maximum load: Sliding door 1 door Sliding door 2 doors	100 kg 2 x 90 kg	100 kg 2 x 90 kg
Maximum opening and closing speed: Sliding door 1 door Sliding door 2 doors	0,8 m/s 1,6 m/s	0,8 m/s 1,6 m/s
Duty class Intermittent operation	Continuous operation S3 = 100%	Continuous operation S3 = 100%
Internal durability test Direct-drive brushless motor with no reduction gear unit		
Power supply Rated power Stand-by	100–240 Vac 50/60 Hz 70 W 10 W	100–240 Vac 50/60 Hz 70 W 10 W
Rated load	150 N	150 N
Protection Rating	IP 20	IP 20
Operating temperature	 -15 °C  +50 °C	 -15 °C  +50 °C
Parameter adjustment	Buttons and Display	Buttons and Display
Connections to control and safety devices	Dedicated connecting terminals	Dedicated connecting terminals
Number of programmable terminals	4 (G1, G2, G3, G4)	4 (G1, G2, G3, G4)
Power output for accessories	12 Vdc (1 A max)	12 Vdc (1 A max)
Memory for settings and data saving	USB standard	USB standard
Function selector device	FSD5, FSD6	FSD5, FSD6
Locking device	SL5LD, SL5SB3, SL5SB4	SL5LD, SL5SB3, SL5SB4
Signal device of lock position	SL5SL	SL5SL (required if SL5LD)
Battery power device for emergency opening	SL5BD, SL5BD1, SL5BD2	SL5BD2 (required)
Fixing device for opening and safety sensor on doorway and on sides	SL5FS, SL5FS3	SL5FS, SL5FS3